

DECKHAND®



Strong, safe, and versatile, the DECKHAND® revolutionizes the way contractors handle loads. Unmatched speed and precision out-performs all other material handling methods.

- Head unit mounts to any brand of excavator in the 20-36 metric ton class
- 360° Continuous Rotation
- Tilts up to 20°
- Shifts load side to side up to 5" in either direction
- Load locking valves hold load securely, regardless of hydraulic pressure
- In-cab display allows operator to safely monitor and adjust all functions, working parameters, and hydraulic settings from inside the excavator.
- Requires auxiliary hydraulic circuit on excavator and dedicated case drain line
- Designed to meet ASME Below-The-Hook Lifting Standards



DECKHAND® HEAD UNIT

Part Number	3815
Model Number	DH4
Excavator Wt Class	20-36 METRIC TON
Supply Pressure	3,000 PSI / 207 BAR
Standard Recommended Flow	25 GPM / 95 LPM
Max Flow	30 GPM / 114 LPM
Min Flow	20 GPM / 76 LPM
Main Beam Size (inches)	6x6
Capacity	30,000 LBS / 13,608 KGS
Weight	2,900 LB / 1,315 KG
Overall Dimensions	100L x 47W x 97H (IN) / 254L x 119W x 246H (CM)
Shipping Storage Stand	1270
Shipping Weight w/ Stand	3,714 LB / 1,685 KG